


8' Split Face Masonry Wall or Chain Link Fence w/ Vinyl Privacy Panels or Equivalent Surrounding the Dumpster Pad
 The privacy fence/wall may be on the inside or outside of the pad as long as a 14'-0" minimum opening is maintained.

- Notes:
1. The surrounding area must be sloped away from the dumpster pad. Intrusion of rainwater from surrounding areas is a contravention of city and state regulations.
 2. A 1' minimum turn down slab is required where the dumpster pad abuts unpaved areas.
 3. The owner is advised to have a Professional Engineer verify that this generic design is suitable for the existing ground conditions, as well as the anticipated wheel loads.
 4. Split face block wall construction must conform to the City of Elizabethton building codes.
 5. The approach to the dumpster pad must have minimum 40'-0" clear space to allow the refuse truck to pull straight in. See detail 3-3

1 Single Enclosure Dumpster Pad
 1 1/4"=1'



City of Elizabethton
 Engineering Department
 Single Wet Dumpster Pad

Designed	Matt J. Balogh	Date	10/19/12	File No.	*dump_pad.DWG
Drawn	Matt J. Balogh		10/19/12	Drawing No.	
Checked	J. Coetzee		10/19/12	Job Class	
Approved				Sheet	1 of 3