

TENNESSEE DEPARTMENT OF ENVIRONMENT & CONSERVATION FILE NO. - 7.16 PERMEABLE GEOTEXTILE FABRIC PERMEABLE
GEOTEXTILE
FABRIC



CONCRETE WASHOUT SIGN (OR EQUIVALENT)

WOOD POST -LAG SCREWS CONCRETE PLYWOOD PAINTED WHITE - LETTERS

SECTION B-B





TYPE "BELOW GRADE"

PLAN VIEW NOT TO SCALE

BERM

NOTES:

1. ACTUAL LAYOUT DETERMINED IN THE FIELD.

2. SIGNAGE IDENTIFYING THE CONCRETE WASHOUT AREA SHALL BE INSTALLED WITHIN 5FT.OF THE WASHOUT FACILITY.

EROSION CONTROL PLAN LEGEND CONCRETE WASHOUT

TYPE "ABOVE GRADE" WITH EATHERN BERMS

NOT TO SCALE

7.16


CONCRETE WASHOUT

_	1	1	1	TYPE
ı	ı	ı	ı	YEAR
ı	1	1	1	PROJECT NO.
ı	1	1	ı	SHEET No.

PLAN VIEW NOT TO SCALE

REV. -






INVIRONMENT AND CONSERVATION

CHECK DAM

NOT TO SCALE

7.20

FILE NO. - 7.21



EROSION CONTROL PLAN LEGEND:

DEWATERING STRUCTURE

#57 STONE

-STRAWBALE -SILT FENCE

-- WOOD STAKE OR STEEL POST

→ 30" MAX. → HEIGHT → POLYETHYLENE SHEETING

PLAN VIEW

2'± <u>ښ</u>

OPTIONAL EXCAVATION

BACKFILL WITH COMPACTED SOIL

SECTION A-A

ANCHOR FILTER CLOTH FABRIC 6" DEEP WITH 4" RUN-OUT LENGTH

TRENCHING DETAIL

4	3	2	PUMP DIAMETER (INCHES)	DEWATERING
500	260	140		STRUCTURE
296	154	83	STORAGE VOLUME REQD (CUBIC YARDS)	DEWATERING STRUCTURE VOLUMES AND DIMENSIONS
57' × 57'	41' × 41'	30' × 30'	INTERIOR	DIMENSIONS

PROJECT NO.

652

1,100

85' X 85'


1. DIMENSIONS BASED ON THE MAXIMUM STRUCTURE HEIGHT OF 30" AND THE LENGTH BEING EQUAL TO THE WDTH. OPTIONAL EXCAVATION IS NOT INCLUDED.
2. ADJUSTMENTS SHOULD BE MADE TO THE DIMENSIONS TO OBTAIN THE BEST CONFIGURATION FOR THE PROJECT SITE. DIMENSIONS ARE BASED ON THE DEWATERING STRUCTURE BEING HORIZONTAL.

E T
NON
NA D
NE PA
NATION TO SERVICE OF THE PARTIES OF

SILT FENCE AND STRAW DEWATERING PIT NOT TO SCALE

DEWATERING PRACTICES (1)


7.21




FILE NO. - 7.22












NOT TO SCALE

DIVERSION

ı	ı	1	ı	TYPE
ı	ı	ı	ı	YEAR
1	1	-	1	PROJECT NO.
1	1	ı	1	SHEET No.

REV. -

FILE NO. - 7.23



CULVERT FLOW (LOW TAILWATER CONDITIONS)

EROSION CONTROL PLAN LEGEND: OP

HC = HEIGHT OF CULVERT

WC = WIDTH OF CULVERT

LA = LENGTH OF RIP-RAP APRON

LA = WIDTH OF RIP-RAP APRON AT END

DSO = MEDIAN RIP-RAP SIZE

DMAX = MAXIMUM SIZE OF RIP-RAP = 1.5 DSO

DA = DEPTH OF RIP-RAP APRON = 1.5 DMAX

SEPARATIOR = GEOTEXTILE UNDERLAYMENT OR GRAVEL

FILTER BLANKET

CULVERT FLOW (HIGH TAILWA TAILWATER > HEAVY GEOTEXTILE FABRIC, ANCHORED 0.5 Hc AND ASSUMING FULL TER CONDITIONS)

 $-D_A = 1.5 \times 1.5 \times D_{50}$ SEPARATOR

MIN. APRON WIDTH = 3 WC

WA = WC + 0.4 LA

—END SECTION, CONCRETE FLOOR OR RIPRAP (TYP)

NOT TO SCALE


7.23

OUTLET PROTECTION



FILE NO. - 7.24

#### TEMPORARY BERM DETAILS







4.5' MIN.



SIDE VIEW



# TEMPORARY SLOPE DRAIN WITH BERM AND RIP-RAP



SLOPE DRAIN

ENT.	
VIRON S	
NT AD	
E PART	
MENI	
100	

	,	,		<b>코</b>
Ì		Ĺ	Ĺ	TYPE
_	1	1	_	YEAR
1	ı	ı	1	PROJECT NO.
ī	1	ı	ī	NO.


REV. -

EROSION CONTROL PLAN LEGEND:


NOT TO SCALE

7.24


FILE NO. - 7.25



### PLAN VIEW FOR DITCH APPLICATION







EROSION CONTROL PLAN LEGEND: --- ) --- ) TUBES AND WATTLES


- (1) THE DEPTH AND MIDTH OF THE WEIR SECTION OF THE WATTLE SHALL BE DESIGNED TO PASS THE 2yr/24hr OR 5yr/24hr STORM EVENT WITHOUT OVERTOPPING THE CHANNEL.
- (2) STAKE PER MANUFACTURERS RECOMMENDATIONS

REV	ı
	г

1	1	ı	ı
1	1	ı	1
1	1	ı	1
NO.	PROJECT NO.	YEAR	TYPE

NOT TO SCALE

TUBES AND WATTLES



PROJECT NO.

4%-6%

6%-8% 8%-10%

S

0.20

0.07

0.04

DESIGN Q = 7 cfs  $S_d = 6\%$ 


L = 7/0.20 = 35 FEETD = 2.5 FEET


LEVEL SPREADER

7.26

TENNESSEE DEPARTMENT OF ENVIRONMENT & CONSERVATION FILE NO. - 7.27 EROSION CONTROL PLAN LEGEND: \_\_\_\_\_\_ ROLLED EROSION CONTROL PRODUCTS ANCHOR TRENCH BACKFILED & COMPLETED SOIL FLOW - STAPLE 1.0' ON CENTER DETAIL SLOPE INTERRUPTION CHECK SLOT FLOW SEE NOTE H SEE ANCHOR TRANCH DETAIL - ROLLED EROSION CONTROL PRODUCTS ALTERNATE ANCHOR NOT TO SCALE CHANNEL 7.27

FILE NO. - 7.28





SECTION B-B



CONSTRUCTION EXIT

o 1					
	ı	ı	ı	ı	TYPE
	ı	ı	ı	ı	YEAR
	1	1	1	1	PROJECT NO.
	1	1	1	ı	NO.

THANRONALIST PARTY COMSTRUCTION
EXIT WITH
WATER BAR

FILE NO. - 7.28

A

SO' MIN.

SO' MIN.

CLEAN WASHED STONE SIZES FROM 2"

TO 4" 8" DEPTH WITH GEOTEXTILE FABRIC


TEMPORARY DRAINAGE

PIPE WHERE NEEDED

DI ANI VIEW OF TEMPORARY DRAINAGE

PIPE WHERE NEEDED

PLAN VIEW OF TEMPORARY CONSTRUCTION ROAD



SECTION A-A




NOT TO SCALE

CONSTRUCTION EXIT





REV	ı	1	ı	1	TYPE
	ı	ı	ı	ı	YEAR
	1	ı	ı	-	PROJECT NO.
	ī	1	1	ī	NO.

FILE NO. - 7.29










SECTION B-B







WATER SUPPLY & HOSE -

Œ

NOTE:
MANY DESIGNS CAN BE FIELD
FABRICATED, OR FABRICATED
UNITS MAY BE USED.

WASH RACK -





TE N N E
NAME OF THE STATE
DE PA
RIMERY
ATION

REV	-	1	-	1	TYPE
	ı	ı	ı	ı	YEAR
	1	1	1	-	PROJECT NO.
	ī	ī	ı	ī	SHEET No.

NOT TO SCALE


TIRE WASHING FACILITY





FILE NO. - 7.32

TOE OF DITCH



PLAN VIEW SMALLER CLEAN STONE- ROCK CHECK DAM

L TOP OF DITCH (NATURAL GROUND) — CENTERLINE OF DITCH FLOW FLOW LENGTH OF SEDIMENT TRAP = EDGE OF WET STORAGE LEDGE OF WET STORAGE SLOPE MAX 2:1 3' MAX. - MACHINED RIPRAP (NATURAL GROUND) — TOE OF DITCH SLOPE -EDGE OF GEOTEXTILE FABRIC FLOW FLOW

FLOW


NOT TO SCALE

EROSION CONTROL PLAN LEGEND:

SEDIMENT TRAP



FILE NO. - 7.33




NOT TO SCALE

ı	ı	1	1	TYPE
ı	ı	ı	ı	YEAR
-	-	-	-	PROJECT NO.
1	1	1	1	SHEET No.

POROUS BAFFLE


FILE NO. - 7.34




NOT TO SCALE SILT FENCE 7.34


EROSION CONTROL PLAN LEGEND: SILT FENCE

ı	ı	1	ı	TYPE
ı	ı	ı	ı	YEAR
ı	1	ı	ı	PROJECT NO.
				_ 4





HARDWARE CLOTH AND GRAVEL INLET PROTECTION (FLOW FROM ONE SIDE)




EROSION CONTROL PLAN LEGEND:

EXCAVATED INLET PROTECTION

HARDWARE CLOTH AND GRAVEL INLET PROTECTION

ROCK RING INLET PROTECTION

REV	ı	ı	ı	ı	TYPE
	1	1	ı	1	YEAR
	1	-	-	-	PROJECT NO.
	1	1	1	1	SHEET NO.




PROJECT NO.



FILE NO. - 7.37

MAX. DISTURBED AREA= ‡ AC / 100' WATTLE



NOT TO SCALE


EROSION CONTROL PLAN LEGEND: --- ) --- )

TUBES AND WATTLES

1	ı	ı	TYPE
T	ı	ı	YEAR
-	1	1	PROJECT NO.
1	ī	1	SHEET No.

THUNDSMINT AND CONSERVATI

FILE NO. - 7.38






PROJECT NO.

FILTER BERM

EROSION CONTROL PLAN LEGEND: -



LINING LIMITS


TEMPORARY PLUG (SANDBAGS, PLYWOOD, JERSEY BARRIER, OR SHEET PILING)

WITHIN EXISTING STREAM CULVERT CONSTRUCTED

OUTSIDE EXISTING STREAM CULVERT CONSTRUCTED


PROPOSED CHANNEL TO BE CONSTRUCTED AFTER COMPLETION OF PERMANENT CULVERT

-- PLACE RIPRAP AT TRANSITION



TEMPORARY STREAM DIVERSION


FILE NO. - 7.43




## PLAN VIEW OF TEMPORARY CULVERT CROSSING

CONSTRUCTION ROAD RUNOFF MUST NOT ENTER STREAMS. PROVIDE OVERFLOW AREA ADJACENT TO THE ACCESS ROAD. WATERBARE DIVERSIONS MAY NOT BE LOWER THAN THE CROWN OF THE TEMPORARY CULVERT.

GEOTEXTILE FABRIC SHALL
BE PLACED UNDER ENTIRE
WIDTH OF MINERAL
AGGREGATE (SIZE 57)





C=1/2 Diameter of PIPE or 18" whichever is greater N=1/2 diameter of PIPE or 12" whichever is greater D = PIPE DIAMETER

SECTION A-A

GEOTEXTILE FABRIC
SHALL BE PLACED ON THE
STREAM BED AND BANKS
PRIOR TO PLACEMENT OF
CULVERTS AND AGGREGATE

.MACHINED RIPRAP (CLASS A-1)

CROWN OF FILL SHOULD BE ABOVE CHANNEL BANKS



_					
REV	ı	ı	ı	1	TYPE
	1	1	1	1	YEAR
	ı	1	1	-	PROJECT NO.
	ı	ı	1	ı	NO SHEE

TEMPORARY STREAM CROSSING