



NOTES:

1. WHERE CONDITIONS DIFFER FROM THOSE SHOWN, UTILITIES MAY BE LOCATED WITHIN THE SIDEWALK SECTION WITH THE APPROVAL OF THE GOVERNING AGENCY.
2. WHEN FIRE HYDRANTS AND LIGHT STANDARDS ARE IN THE SAME VICINITY, THEY SHALL BE SEPARATED BY AT LEAST 5 FEET.
3. WHEN STOP SIGN IS LOCATED AT P.C., STREET SIGNS SHALL BE MOUNTED ON SAME POLE.
4. STREET SIGNS AT MID-RETURN SHALL BE LOCATED ADJACENT TO A PEDESTRIAN CURB RAMP, IF APPLICABLE.
5. WHERE CURB AND GUTTER DO NOT EXIST, EDGE OF STOP SIGN SHALL BE PLACED AT THE BEGINNING OF THE CURVE, 6 FEET FROM THE EDGE OF PAVEMENT.

NO.	REVISION	DATE	STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION FIRE HYDRANT & STREET LIGHT LOCATIONS	SECTION UTILITIES	
				DRAWING NO. U-1.1	
			CITY OF ELKO, NEVADA	DATE 11/30/07	PAGE 1